

WCHX 25269

O U T A G E GAUGE TABLE

Page 80

NK EC I 25000-26999 GAL NP Shell Full: 25521
 Tank Serial #: 526431 Compartment: 1 2% Outage: 510

| Inches | 0 Feet | 1 Foot | 2 Feet | 3 Feet | 4 Feet | 5 Feet | 6 Feet | 7 Feet |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0.00 | 0 | 1811 | 4563 | 7820 | 11338 | 14924 | 18392 | 21540 |
| 0.25 | 13 | 1861 | 4627 | 7891 | 11413 | 14999 | 18462 | 21600 |
| 0.50 | 36 | 1911 | 4690 | 7962 | 11488 | 15073 | 18531 | 21660 |
| 0.75 | 59 | 1962 | 4755 | 8034 | 11563 | 15147 | 18601 | 21720 |
| 1.00 | 84 | 2013 | 4819 | 8106 | 11637 | 15221 | 18670 | 21780 |
| 1.25 | 109 | 2064 | 4883 | 8178 | 11712 | 15294 | 18739 | 21840 |
| 1.50 | 136 | 2116 | 4948 | 8249 | 11787 | 15368 | 18808 | 21899 |
| 1.75 | 163 | 2168 | 5013 | 8321 | 11862 | 15442 | 18877 | 21958 |
| 2.00 | 191 | 2221 | 5078 | 8394 | 11936 | 15516 | 18945 | 22016 |
| 2.25 | 220 | 2274 | 5144 | 8466 | 12011 | 15589 | 19014 | 22075 |
| 2.50 | 250 | 2327 | 5209 | 8538 | 12086 | 15663 | 19082 | 22133 |
| 2.75 | 280 | 2380 | 5275 | 8610 | 12161 | 15736 | 19150 | 22191 |
| 3.00 | 312 | 2434 | 5341 | 8683 | 12236 | 15810 | 19218 | 22248 |
| 3.25 | 344 | 2488 | 5407 | 8755 | 12311 | 15883 | 19286 | 22305 |
| 3.50 | 376 | 2543 | 5473 | 8828 | 12386 | 15957 | 19353 | 22362 |
| 3.75 | 410 | 2598 | 5539 | 8901 | 12461 | 16030 | 19421 | 22419 |
| 4.00 | 444 | 2653 | 5606 | 8974 | 12535 | 16103 | 19488 | 22475 |
| 4.25 | 478 | 2708 | 5673 | 9047 | 12610 | 16176 | 19555 | 22531 |
| 4.50 | 513 | 2764 | 5740 | 9120 | 12685 | 16249 | 19622 | 22587 |
| 4.75 | 549 | 2820 | 5807 | 9193 | 12760 | 16322 | 19689 | 22643 |
| 5.00 | 586 | 2877 | 5874 | 9266 | 12835 | 16395 | 19756 | 22698 |
| 5.25 | 623 | 2933 | 5942 | 9339 | 12910 | 16467 | 19822 | 22753 |
| 5.50 | 660 | 2990 | 6009 | 9412 | 12985 | 16540 | 19888 | 22807 |
| 5.75 | 699 | 3047 | 6077 | 9486 | 13060 | 16613 | 19954 | 22861 |
| 6.00 | 737 | 3105 | 6145 | 9559 | 13135 | 16685 | 20020 | 22915 |
| 6.25 | 777 | 3163 | 6213 | 9633 | 13209 | 16757 | 20086 | 22969 |
| 6.50 | 816 | 3221 | 6282 | 9706 | 13284 | 16830 | 20152 | 23022 |
| 6.75 | 857 | 3279 | 6350 | 9780 | 13359 | 16902 | 20217 | 23075 |
| 7.00 | 898 | 3338 | 6419 | 9853 | 13434 | 16974 | 20282 | 23128 |
| 7.25 | 939 | 3397 | 6487 | 9927 | 13509 | 17046 | 20347 | 23180 |
| 7.50 | 981 | 3456 | 6556 | 10001 | 13584 | 17118 | 20412 | 23232 |
| 7.75 | 1023 | 3515 | 6625 | 10075 | 13658 | 17190 | 20476 | 23283 |
| 8.00 | 1066 | 3575 | 6694 | 10149 | 13733 | 17261 | 20540 | 23334 |
| 8.25 | 1109 | 3635 | 6764 | 10223 | 13808 | 17333 | 20605 | 23385 |
| 8.50 | 1153 | 3695 | 6833 | 10297 | 13882 | 17404 | 20669 | 23436 |
| 8.75 | 1197 | 3755 | 6903 | 10371 | 13957 | 17476 | 20732 | 23486 |
| 9.00 | 1242 | 3816 | 6973 | 10445 | 14032 | 17547 | 20796 | 23535 |
| 9.25 | 1287 | 3877 | 7043 | 10519 | 14106 | 17618 | 20859 | 23585 |
| 9.50 | 1332 | 3938 | 7113 | 10594 | 14181 | 17689 | 20922 | 23634 |
| 9.75 | 1378 | 4000 | 7183 | 10668 | 14255 | 17760 | 20985 | 23682 |
| 10.00 | 1425 | 4061 | 7253 | 10742 | 14330 | 17831 | 21047 | 23730 |
| 10.25 | 1472 | 4123 | 7323 | 10817 | 14404 | 17901 | 21110 | 23778 |
| 10.50 | 1519 | 4185 | 7394 | 10891 | 14479 | 17972 | 21172 | 23825 |
| 10.75 | 1567 | 4248 | 7465 | 10966 | 14553 | 18042 | 21234 | 23872 |
| 11.00 | 1615 | 4310 | 7535 | 11040 | 14628 | 18113 | 21295 | 23919 |
| 11.25 | 1663 | 4373 | 7606 | 11115 | 14702 | 18183 | 21357 | 23965 |
| 11.50 | 1712 | 4436 | 7677 | 11189 | 14776 | 18253 | 21418 | 24011 |
| 11.75 | 1761 | 4499 | 7748 | 11264 | 14850 | 18323 | 21479 | 24056 |

ATTENTION

Measurements made using these tables should be verified initially by comparing to metered quantity of product or other means (such as weight).
 Capacities shown indicate US gallons out of tank at given outage dimension measured from inside top of shell to liquid level at center of tank.

WCHX 25269

O U T A G E GAUGE TABLE

Page 81

NK EC I 25000-26999 GAL NP
1 Compartment: 1

Shell Full: 25521
2% Outage: 510

| Inches | 8 Feet | 9 Feet |
|--------|--------|--------|
| 0.00 | 24101 | 25496 |
| 0.25 | 24145 | 25502 |
| 0.50 | 24189 | 25507 |
| 0.75 | 24232 | 25511 |
| 1.00 | 24275 | 25514 |
| 1.25 | 24318 | 25517 |
| 1.50 | 24360 | 25519 |
| 1.75 | 24401 | 25520 |
| 2.00 | 24442 | 25521 |
| 2.25 | 24483 | 25521 |
| 2.50 | 24523 | 25521 |
| 2.75 | 24562 | |
| 3.00 | 24601 | |
| 3.25 | 24640 | |
| 3.50 | 24678 | |
| 3.75 | 24715 | |
| 4.00 | 24752 | |
| 4.25 | 24788 | |
| 4.50 | 24823 | |
| 4.75 | 24858 | |
| 5.00 | 24892 | |
| 5.25 | 24926 | |
| 5.50 | 24959 | |
| 5.75 | 24991 | |
| 6.00 | 25023 | |
| 6.25 | 25054 | |
| 6.50 | 25084 | |
| 6.75 | 25114 | |
| 7.00 | 25143 | |
| 7.25 | 25170 | |
| 7.50 | 25198 | |
| 7.75 | 25224 | |
| 8.00 | 25249 | |
| 8.25 | 25273 | |
| 8.50 | 25297 | |
| 8.75 | 25319 | |
| 9.00 | 25340 | |
| 9.25 | 25360 | |
| 9.50 | 25379 | |
| 9.75 | 25396 | |
| 10.00 | 25412 | |
| 10.25 | 25426 | |
| 10.50 | 25440 | |
| 10.75 | 25452 | |
| 11.00 | 25463 | |
| 11.25 | 25473 | |
| 11.50 | 25482 | |
| 11.75 | 25489 | |

ATTENTION

Measurements made using these tables should be verified initially by comparing to metered quantity of product or other means (such as weight). Capacities shown indicate US gallons out of tank at given outage dimension measured from inside top of shell to liquid level at center of tank.